

CURRENT DETECTING DEVICE

Publication number: JP2001165963

Publication date: 2001-06-22

Inventor: OTSUKA KOJI

Applicant: SANKEN ELECTRIC CO LTD

Classification:

- International: G01R15/20; H01L43/06; G01R15/14; H01L43/06;
(IPC1-7): G01R15/20; H01L43/06

- European: H01L43/06B

Application number: JP19990350063 19991209

Priority number(s): JP19990350063 19991209

Also published as:



EP1107328 (A2)

US6462531 (B1)

EP1107328 (A3)


EP1107328 (B1)

Report a data error here

Abstract of JP2001165963

PROBLEM TO BE SOLVED: To solve such problem that detection of a large current with high accuracy using a Hall element was difficult.

SOLUTION: A conductor layer 15 as a current passage is placed on an insulating film 32 of the surface of a semiconductor base constituting a Hall element 1. This conductor layer 15 is placed, so as to surround a main operation area of the Hall element 1. The Hall element 1 and terminals 3, 4 of first and second current passages are molded with a common resin-sealing substance 18 as a unit. A wire 12 is connected as a current passage for a first resistor R1 between the terminals 3, 4 for the first and second current passages, and also the conductor layer 15 by wires 13, 14 for forming the second current passage.



Data supplied from the esp@cenet database - Worldwide

EP1107328